



2026 Ford Mustang Cup Classic

Technical Regulations

Version 1

01/14/2026

Table of Contents

ARTICLE 1: SUMMARY OF TECHNICAL REGULATIONS.....	4
1.1 CLASS ELIGIBILITY	5
ARTICLE 2: DRIVER EQUIPMENT	5
2.1 GENERAL	5
2.2 FRONTAL HEAD RESTRAINT SYSTEM.....	7
2.3 DRINKING SYSTEMS	8
ARTICLE 3: GENERAL REGULATIONS.....	9
3.1 TECHNICAL INSPECTION (SCRUTINEERING)	9
ARTICLE 4: SAFETY.....	12
4.1 DRIVER SAFETY HARNESS SYSTEM	12
4.2 SEAT	12
4.3 HELMET SUPPORT NETS	12
4.4 DRIVER WINDOW NET	13
4.5 PROTECTIVE PADDING	13
4.6 MASTER ELECTRICAL SWITCHES	14
4.7 FIRE SUPPRESSION SYSTEM	14
ARTICLE 5: VEHICLE SYSTEMS	15
5.1 MODIFICATIONS TO THE SPECIFICATIONS	15
5.2 SERVICING, REPAIR, AND REPLACEMENT	16
5.3 DIMENSIONS	16
5.3.1 General	16
5.3.2 Mass	17
5.3.3 Ballast.....	20
5.3.4 Minimum Ride Height	20
5.4 CHASSIS	21
5.4.1 General	21
5.4.2 Air Jack System	21
5.5 DRIVER INTERFACE	21
5.5.1 General	21
5.5.2 Pedal Box.....	22
5.5.3 Driver Cooling Systems.....	22
5.5.4 Driver Ventilation Ducts	22
5.6 BODYWORK	23
5.7 ENGINE SYSTEM	23
5.7.1 Engine System Restriction Measures	24
5.8 DRIVE SYSTEM	24
5.9 COOLING SYSTEM	25
5.10 FUEL SYSTEM	25
5.10.1 Fuel Cell	25
5.10.2 Approved Fuel Cell Requirements	25
5.11 BRAKE SYSTEM.....	26

5.12 SUSPENSION SYSTEM	27
5.12.1 Springs	27
5.13 WHEELS AND TIRES	27
5.14 POWER OUTPUT REGULATIONS	27
5.14.1 Testing Requirements	27
5.14.2 Vehicle Setup	29
5.14.3 Power Requirements	29
5.14.4 Weight to Power Ratio	29
5.14.5 Performance and Power Balancing	30
ARTICLE 6: SERIES REQUIRED ELECTRONIC SYSTEMS.....	30
6.1 TRANSPONDERS	30
6.2 MYLAPS X2 DRIVER ID (TWO-DRIVER ENTRIES).....	31
6.3 RACELINK GPS/IN-CAR FLAGGING UNIT	31
6.4 IN-CAR FLAGGING DISPLAY – T DASH XL	31
6.5 RADIO COMMUNICATIONS	31
6.5.1 Team Pit-to-Car Radio	31
6.5.2 Team Frequencies.....	32
6.5.3 USAC Race Control Frequency.....	32
6.6 ON-BOARD VIDEO & STREAMING	33
ARTICLE 7: REFUELING SYSTEM.....	33
7.1 SCRUTINEERING FUEL COLLECTION	33
ARTICLE 8: PROHIBITED CHANGES TO THE VEHICLE SYSTEMS AFTER APPROVAL.....	35
8.1 DIMENSIONS	35
8.8 FUEL SYSTEM	35
8.2 OVERALL DIMENSIONS.....	35
8.9 BRAKE SYSTEM	35
8.3 DRIVER INTERFACE	35
8.10 STEERING SYSTEM	35
8.4 AERODYNAMIC ELEMENTS	35
8.11 SUSPENSION SYSTEM	35
8.5 ENGINE SYSTEM	36
8.12 WHEELS AND TIRES	36
8.6 DRIVE SYSTEM	36
8.13 ELECTRONICS	36
8.7 COOLING SYSTEM	36

Article 1: Summary of Technical Regulations

The Ford Mustang Cup Classic is an official one-make class.

Only cars of the below type and make that fully comply with these Technical Regulations as well any other official USAC or Ford Racing documentation are eligible to participate.

2005-2008 Ford Mustang FR500S

2005-2008 Ford Mustang FR500C

2012-2014 Ford Mustang Boss 302S

2012-2014 Ford Mustang Boss 302R

2017 Ford Mustang FP350S

It is the Entrant's responsibility to ensure that the car remains unchanged to represent the approved vehicle configuration at all times during events sanctioned by USAC including:

- As-Approved Configuration
 - Unless otherwise instructed within these Technical Regulations, Ford Motor Company, or USAC, the vehicle must remain unchanged after receiving series approval from Ford Motor Company. The approval sign-off document is specific to and defined by the Manufacturer, Ford Motor Company, and approved by USAC.

Should a change of car be necessary, the change must be applied for in writing using the appropriate forms and documentation prior to the change. The approval of the change is at the discretion of USAC. Should the application be accepted, specific conditions may be given. Should the application be submitted for and approved following a qualifying session, additional penalty may follow.

1.1 Class Eligibility

Vehicles will be entered into the **Cup Classic** class.

Article 2: Driver Equipment

2.1 General

Driver safety equipment must always be worn when seated in the car, whether in the pre-grid area, pit lane, or on the track. It is mandatory for drivers to wear overalls that meet the FIA 8856-2000 or FIA 8856-2018 standards, along with appropriate underwear (long sleeves and legs), balaclava, socks, shoes, and gloves in accordance with FIA regulations.

Drivers must wear high-quality full-face helmets that include a visor. Helmets must comply with one of the following FIA standards: 8859-2015, 8860-2010, or 8860-2018, or the Snell SA2015 standard. Any modifications, such as drilling holes, are prohibited and will invalidate the homologation.

Drivers must also ensure their helmets are equipped with a helmet removal kit, such as the "Eject Helmet Removal" system, the Stand 21 "Lid Lifter Balaclava," or the ROUX helmet removal system, as specified by the manufacturer.

All drivers are required to wear overalls, gloves, underwear, balaclava, socks, and shoes that are homologated to the FIA 8856-2000 or SFI 3.2A/5 standards.

Regardless of the number of layers in a suit, it is mandatory to wear fire-resistant underwear made from NOMEX® or Carbon-X.

Although items from any manufacturer may fail inspection due to wear and tear over time, FIA homologated equipment will no longer be valid for use after December 31st of the calendar year that marks ten (10) years from the manufacture date indicated on the FIA label, or after December 31st of the expiration year listed on the FIA label.

2.2 Frontal Head Restraint System

Drivers are required to wear a Frontal Head Restraint (FHR) that meets the FIA 8858-2002 or 8858-2010 standards. It is highly recommended for drivers to use helmets with tether anchorages that are fitted as original equipment by the manufacturer. FIA homologated tethers with an FIA 8858-2002 label are mandatory and must not be used after December 31st of the manufacturer's declared expiration year.

Sternum straps are not permitted for use with the HANS system due to potential interference. Only HANS-specific two-inch hybrid shoulder straps that comply with FIA, SFI 16.1, or SFI 16.5 harness certifications are allowed to be used with this system.

Any HANS device must display a Silver and Blue SFI 38.1 Sticker or a Silver and Black FIA 8858-2002/2010 sticker. The SFI sticker will have a punched date showing the month and year of certification.

Head and Neck Restraint Devices bearing only a Black FIA 8858-2002/2010 sticker (without an SFI sticker) must have their tethers replaced five (5) years after the manufacturing date on the label.

Head and Neck Restraint Devices certified to SFI Spec. 38.1 must undergo inspection and re-certification every five (5) years, starting January 1, 2012. The device must be returned to the original manufacturer for inspection five (5) years from the date of manufacture marked on the label. If the manufacturer deems the device safe for continued use, a new SFI 38.1 conformance label with the inspection date will be applied, and the device will be valid for another five (5) years.

All head and neck restraint devices must be inspected following any serious incident. If there is any cracking, delamination, or elongation, the device must be replaced.

Devices claiming to meet SFI or FIA specifications but lacking an official SFI or FIA certification sticker are not approved.

Drivers must present their complete safety equipment for inspection during Technical Inspection.

2.3 Drinking Systems

A drinking system is permitted. Installation is subject to the approval of the tech manager.

Article 3: General Regulations

No expressed or implied safety warranty shall be provided because of this inspection or approval. It remains the sole responsibility of the competitor to ensure their car is free from mechanical defects and in a safe racing condition. Cars that are damaged or modified after being approved during inspection must undergo re-inspection and approval. USAC officials will have the final authority in determining the safety and eligibility of a vehicle that has been involved in an accident.

Major body components must remain in their normal position throughout the competition. Any cars in question will be subject to approval by the Technical Director.

Cars must maintain a neat, clean, and professional appearance always.

3.1 Technical Inspection (Scrutineering)

Competitors are required to present their cars for Technical Inspection upon request by the series Technical Officials at any point during the event. Failure to comply may result in penalties, including exclusion from the event.

Each car entered must undergo inspection and receive approval from the Technical Director or their designated assistant(s) before being allowed to participate in competition or

qualifying. A sign-up sheet for Technical Inspection appointments will be provided. For the first event, sign-ups will be on a "first-come, first-served" basis. For subsequent events, sign-up requests will be scheduled.

USAC, at its sole discretion, reserves the right to impound any car for Technical Inspection at any time during the event. In case of uncertainty, USAC may retain a car after the event until any issues are resolved. This inspection may include disassembling various parts of the car, including the engine. Competitors acknowledge that in order to complete such an inspection, mandatory seals may be broken, and it is their responsibility to replace any broken seals before further competition. Failure to do so may result in penalties.

The timing, location, method, and type of inspection, as well as the number of cars to be inspected, will be determined by the Technical Director.

When instructed by officials, cars must proceed directly to the inspection (Impound) area without delay, accompanied by a team representative. A car that does not proceed immediately to Impound is subject to penalty. No data downloads or tire pressure checks are allowed in the pit lane, and the car may not be touched by the team representative(s) until directed by a series Technical official.

A team representative must be present at Impound to receive any decisions regarding potential technical checks. A maximum of three (3) team representatives per car is allowed at any time unless directed otherwise by a series Technical official.

Team equipment is prohibited in Impound unless directed otherwise by a series Technical official. Similarly, computers or electronic equipment are not allowed in Impound unless specifically authorized by a series Technical official.

It is the responsibility of the Driver or Competitor to ensure the car is prepared for inspection when requested by the Technical Director or their assistants. Any expenses incurred, except in the case of a protest, are the Competitor's responsibility. Preparation must be completed in a timely manner as determined by the Technical Director. Any non-compliant parts may be retained indefinitely by USAC.

Access to inspection areas is controlled by the Technical Director. All cars entered must undergo Technical Inspection during the designated hours, and each vehicle will be assigned a specific time for compliance inspection.

At each event, all driver safety equipment (such as fire suits, helmets, HANS devices, helmet lift systems, etc.) will also be inspected for compliance.

Article 4: Safety

4.1 Driver Safety Harness System

Driver Safety Harness Systems must be installed and maintained as configured during the vehicle signoff.

4.2 Seat

Driver's seat must be installed and maintained as configured during the vehicle signoff.

The materials used for seat inserts must comply with either:

- FIA Technical List 50 (p.18)
- SFI Specification 45.2 (p.19)

Both of these documents can be found at the end of these Technical Regulations.

4.3 Helmet Support Nets

Helmet Support Nets must be installed and maintained as configured during the vehicle signoff.

Installation requirements:

- The installation instructions provided by the supplier and/or manufacturer must be followed.
- The horizontal webbing must be positioned facing the Driver.
- When fastened to anchor points, the nets must be:
 - Aligned parallel to the car's centerline.
 - Positioned with a minimal gap from the Driver's helmet.
- Nets may not have any signage or equipment attached to them.
- Containment nets must be replaced before the expiration date:
 - FIA homologated nets: Immediately after December 31st of the year indicated on the label.

4.4 Driver Window Net

Driver Window Net must be installed and maintained as configured during the vehicle signoff.

4.5 Protective Padding

Protective Padding must be installed and maintained as configured during the vehicle signoff.

4.6 Master Electrical Switches

Master Electrical Switches must be installed and maintained as configured during the vehicle signoff.

The systems must remain operational during all on-track activities or upon USAC's request.

The interior and exterior master switches must be clearly marked with a self-reflective symbol of a red spark, enclosed by a white-edged blue triangle with a base width greater than 30 mm.

4.7 Fire Suppression System

Fire Suppression System must be installed and maintained as configured during the vehicle signoff.

The system must be firmly mounted.

The following must be clearly visible without the need for photography, tools, or removing the seat:

- Pressure gauge (if applicable)
- Manufacturing date
- Date of next required service

The nozzles must not be aimed directly at the Driver's face.

The exterior activation mechanism must be marked with a self-reflective symbol featuring a red edge surrounding a red "E" inside a white circle, with a diameter of at least 100 mm.

USAC may request the removal of the fire bottle for technical inspection.

The entrant is responsible for demonstrating the proper functionality of the interior and exterior fire suppression activation mechanisms, using the "test" mode if available.

Article 5: Vehicle Systems

5.1 Modifications to the Specifications

Entrants are allowed to make the following changes, so long as these technical regulations, all current technical bulletins, and the technical credential are fully adhered to:

- Modify component settings that are specified as adjustable.
- Swap components with parts designated as optional.

Manufacturers are required to submit any declarations specified in these technical regulations using the designated forms.

Additional authorization to alter the specification and/or as-delivered condition is provided through the following formal communication methods:

- Published USAC Technical Bulletin

Informal and/or verbal communication does not constitute valid authorization.

5.2 Servicing, Repair, and Replacement

All servicing or repairs must be carried out in good faith to return the car and all components to their approved original form and function, as defined by the individual vehicle signoff sheets. The entrant of the race vehicle is responsible and liable for all repairs to their corresponding vehicles.

Entrants are allowed to replace damaged or worn components, as long as these Technical Regulations are honored.

5.3 Dimensions

5.3.1 General

USAC's calibrated measurement instruments are considered the official tools for measurement.

Scrutineering measurements are taken with the appropriate dry-type tire set installed.

Tire pressure must be set at **36.0 psi (± 0.5 psi)** for scrutineering measurements.

5.3.2 Mass

The minimum mass for the Car(s) (including driver equalization weight):

- FR500C: 3450 lbs
- FR500S: 3450 lbs
- Boss 302R: 3550 lbs
- Boss 302S: 3550 lbs
- FP350S: 3650 lbs

5.3.2a Determining the Car Weight

The weight of a car includes:

- The weight of the car with an empty fuel tank.
- The weight of all mandated car equipment, or the equivalent substitute ballast.
- The weight of the installed ballast plate and associated hardware (including driver equalization weight).
- The weight of any additional components or systems mandated by USAC.

5.3.2b Official Driver Weight

The official minimum weight of a driver will be determined at the first event of the season or at USAC's request. This weigh in will be conducted on the official USAC scale.

- Each driver must wear the complete driver apparel outlined in these technical regulations during this weigh in.
- Once the driver's weight is recorded by USAC, it becomes the "Official Driver Weight."
- This "Official Driver Weight" will be rounded up to the nearest whole pound.
 - For example, a weight of 180.30 pounds will be rounded to 181.00 pounds.
- For scrutineering purposes, the Official Driver Weight is used for all events, or until such time that the driver is re-weighed.
- Should a driver wish to be reweighed, they may do so at the start of an event and a new "Official Driver Weight" will be recorded, effective starting that event.
- USAC may require a driver to be re-weighed at any time.

It is the Competitor's responsibility to ensure that the combined weight of the installed equalization ballast and their "Official Driver Weight" always meets or exceeds the minimum weight requirement.

5.3.2c Determining the total weight of the Driver and Car

The total combined weight of the car and “Official Driver Weight” will be specified in these technical regulations or in a future bulletin. USAC may, at their discretion, choose to weigh the car and driver separately, together, or substitute the driver for the weighing.

- If the car is weighed without the driver, USAC will add the Official Driver Weight to determine the total weight of the car.
- Before weighing the car and after taking a fuel sample, the team must remove any remaining fuel from the fuel tank under USAC’s direction.

The weighing of the cars is conducted routinely on the official scale, overseen and managed by USAC officials and accounting for the car as-raced.

If, during any post-session weighing procedure, the total weight of the car and driver (including mandatory driver equipment) is found to be below the current minimum weight requirement, the car will be weighed twice more on the same scales, under the same conditions, immediately after the session, and using the same measuring method. The highest of the three recorded weights will be considered the official weight for the car and driver combination (including mandatory driver equipment).

5.3.3 Ballast

Entrants are allowed to add or remove ballast to meet the minimum weight requirement, so long as it is placed in the approved ballast location.

Approved ballast locations can be any of the following:

- Passenger footwell compartment behind the front firewall
- Passenger front seat mounts

Ballast must be in the form of plates or panels. Ballasts must be secured and fastened directly to the chassis through the use of high-strength steel bolts or studs and nuts with large washers.

The addition or removal of ballast during the race is prohibited.

5.3.4 Minimum Ride Height

Ride Height is measured during technical inspection at the specific points outlined in the Homologation Document. The measurement is checked with the ready-to-drive Car, excluding fuel, including the Driver (Or substituted Official Driver Weight) on board.

- All vehicles must maintain a minimum ride height of 85mm from the ground to the front of the chassis splitter

Minimum ride height requirements can only be changed through the release of Technical Service Bulletins from Ford Motor Company or USAC.

5.4 Chassis

5.4.1 General

Only with the approval of USAC, Entrants may make minimal modifications for the installation of approved components.

5.4.2 Air Jack System

Entrants may install an air jack system. Should the entrant choose to install such system, the system must be installed and maintained by the entrant.

5.5 Driver Interface

5.5.1 General

Entrants may install no more than (2) defogging fans and associated ducts

- USAC must approve the installation
- No additional purposes may be served by such systems
- Visibility or cockpit ingress/egress may not be compromised

5.5.2 Pedal Box

Entrants may apply non-slip adhesives to the surface of driver pedals.

5.5.3 Driver Cooling Systems

Entrants may install no more than (2) Driver Cooling Systems, i.e. Cool Suits.

Driver cooling systems must use non-flammable refrigerants, such as R134a or water.

The ballast system can be removed if not required, and a cooling system can be mounted directly to the car in the passenger area.

If installed, driver cooling systems must meet the following requirements:

- The driver cooling system may be mounted to the ballast mounting plate (with the studs and nuts removed).
- an option plate may be used to mount in the rear passenger seat area (outlined in the homologation document).

5.5.4 Driver Ventilation Ducts

Entrants may install Driver Ventilation Ducts

- For the purposed of cooling the driver, a NACA duct may be installed on the side window, or the rear window.

- No more than 2 ducts, 1 per side are permitted per car.
- The cutout area may not exceed 26cm x 16cm.
- The outward plane of the surface on which the duct is installed may not be broken.
- Ducts must be see-through.
- Driver visibility or cockpit ingress/egress may not be compromised

5.6 Bodywork

Tear-off and Anti-fog films may be added to the front windscreen.

Bodywork seams must remain as originally configured.

With USAC's permission, Entrants may apply removable die cut sponsorship decals.

5.7 Engine System

Ford Motor Company or USAC placed seals or required restrictors must remain present, respected and unbroken in the as-configured state following the series vehicle signoff.

5.7.1 Engine System Restriction Measures

Engine systems may require restrictors to meet the power requirements outlined in section 5.14 Power Output Regulations. Acceptable forms of restriction measures include but are not limited to:

- Smaller Throttle bodies
- Pre-Throttle body restrictor inserts
- Post-Throttle body restrictor plates
- Modified Calibrations set prior to the approved dynamometer process outlined in section 5.14 Power Output Regulations

Ford Motor Company and USAC reserve the right to monitor, record, and analyze telemetry, acceleration, and related performance data at any time before, during, or after an event for the purpose of assessing vehicle performance and detecting changes in power characteristics.

5.8 Drive System

Ford Motor Company or USAC placed seals or required restrictors must remain present, respected and unbroken in the as-configured state following the series vehicle signoff.

Lubricants and Fluids: unrestricted.

5.9 Cooling System

Only the following cooling fluids are permitted:

- Water
- Non-glycol based fluids such as Water Wetter

5.10 Fuel System

The exclusive for the Ford Mustang Cup is Sonoco 260GT, as provided by Sonoco fuels.

A fuel sample may be required by USAC for inspection.

5.10.1 Fuel Cell

A fuel cell is required to have the appropriate amount of fuel to finish an entire race session.

5.10.2 Approved Fuel Cell Requirements

All vehicles must be equipped with an FIA-approved FT-3 (or higher specification) fuel cell.

Fuel cells must not be more than 10 years old from the original date of manufacture. Fuel cells that have no verifiable date of manufacture must be recertified by an approved facility prior to racing.

Fuel cell capacities are left open, recommended capacities are no less than 22 gallons and no more than 30 gallons.

The fuel cell must be securely and directly mounted to the vehicle chassis and/or roll cage structure in a manner that prevents movement in all directions under racing conditions.

The fuel cell must be located behind a rear firewall that fully separates the fuel cell from the driver compartment. The firewall must be absent of holes.

The fuel cell must contain a one-way check valve to prevent fuel leakage in the event of a crash or rollover.

The fuel cell is subject to technical inspection approval and scrutineering.

5.11 Brake System

Lubricants and Fluids: unrestricted.

Opaque adhesive tape may be used for the sole purpose of blocking off portions of the brake duct inlet.

5.12 Suspension System

5.12.1 Springs

Springs are left open.

5.13 Wheels and Tires

Valve caps must be securely in place and utilized during all sessions.

Yokohama is the approved tire supplier.

5.14 Power Output Regulations

5.14.1 Testing Requirements

All testing shall be conducted on a Dynojet chassis dynamometer located within a commercial facility, or on a portable Dynojet unit operated as part of a public, commercial business. The Dyno operator shall be an employee of the business and shall not be the vehicle owner, competitor, or any member of the competitor's crew.

A minimum of three (3) consistent and repeatable power runs shall be performed for each permitted power configuration. All graphs shall be printed on a single sheet, displaying

horsepower and torque on the Y-axis and engine speed (RPM) on the X-axis. SAE J1349 Rev. JUN90 correction shall be applied, with a smoothing factor of five (5).

The horsepower/RPM numerical table for the run exhibiting the highest recorded maximum horsepower shall be printed in 50-RPM increments. Horsepower values shall be rounded to the nearest whole number.

All graph and numerical printouts shall clearly identify the date and time of testing; vehicle owner's name; vehicle number; vehicle year/make/model; shop name; shop phone number; and the name of the Dyno operator.

All tests shall be performed in the transmission gear providing a 1:1 ratio.

Each Dyno graph shall show a continuous decline in power for at least 1500 RPM beyond the point of maximum horsepower, or the vehicle shall reach the physical rev-limiter during testing.

5.14.2 Vehicle Setup

Engine speed shall be measured exclusively by an inductive pickup or other direct-reading sensor. Signals obtained from the ECU, OBD port, dashboard display, or tachometer calibration are not permitted.

The vehicle shall be tested only at full and stable operating temperature, representative of normal on-track conditions.

All tires shall be inflated to a minimum cold pressure of 28 psi prior to testing.

The hood shall remain fully open during all testing procedures. A cooling fan shall be positioned in front of the engine and/or radiator to maintain consistent thermal conditions.

Any device installed to restrict airflow within the intake system shall be clearly identified and permanently marked with its dimensional specifications.

5.14.3 Power Requirements

- Measured by the testing procedures as stated in 5.14.1 Testing Requirements. Power requirements are left open so long as they adhere to the specified weight to power ratio specified in section 5.14.4 Weight to Power Ratio

5.14.4 Weight to Power Ratio

Weight to power ratio is calculated by taking the weight determined in section 5.3.2 Mass and dividing that by the peak horsepower figure from section 5.14.1 Testing Requirements. Weight to power ratio is set at 9.7.

5.14.5 Performance and Power Balancing

Ford Motor Company and USAC reserves the right to apply performance adjustments, including but not limited to vehicle weight modifications, air restrictor size, or other technical parameters, at any time to ensure competitive balance within the field.

Article 6: Series Required Electronic Systems

Series required electronic systems must be installed and maintained according to the relevant Homologation and/or Declaration.

The installation, operation, maintenance, and care of these Series required systems is the responsibility of the Entrant.

6.1 Transponders

All Cars must be equipped with a functional MyLaps timing Transponder at all times, mounted in accordance with the Technical Summary Regulations. Any Car with a non-functioning transponder will not receive any official times from any other means and may be ordered to stop and repair immediately, at the sole discretion of the Race Director.

Timing staff may endeavor to score a car with a failed transponder in-race for position only (no lap times). The required transponder is the MyLaps TR2 Direct Power transponder.

6.2 MyLaps X2 Driver ID (Two-Driver Entries)

All two-driver entry cars must utilize the MyLaps X2 Driver ID system.

6.3 Racelink GPS/In-Car Flagging Unit

All cars must be fitted with a functioning MyLaps RaceLink unit, in accordance with these Technical Regulations. Cars with a non-functioning RaceLink may be ordered to stop and repair immediately, at the sole discretion of the Race Director.

6.4 In-Car Flagging Display – T Dash XL

All cars must be fitted with a functioning T Dash XL in-car flagging display, in accordance with these Technical Regulations.

6.5 Radio Communications

6.5.1 Team Pit-to-Car Radio

Only the UHF (450-470 MHz) frequency band is permitted for pit to Car radio communication. Competitor radio traffic is limited to a maximum of four (4) watts on handheld radios and a maximum of ten (10) watts ERP on mobile units (base stations) and/or repeaters and must not transmit to Car on one frequency and receive on another at greater than 5Mhz spacing. All Car communication must operate or be rebroadcast in

analog mode on 12.5Khz channel spacing. On the transmit and receive of a radio broadcast, the DPL or TPL codes must be the same. Mixing of codes between TX and RX is prohibited. Encrypted or any other radio transmission scheme between Team and Driver not understandable using a standard scanner at any time during any qualifying Session or Race is prohibited.

6.5.2 Team Frequencies

Teams must declare and register their Team-to-Driver radio frequency used in any qualifying Session and Race. The USAC designated partner is Racing Radios. Teams must submit frequency registrations directly to USAC no later than two (2) weeks prior to their first Race and at each Race if changed. Changes during an Event must be submitted no less than two (2) hours prior to qualifying or Race.

Car-to-car radio transmission or communication between Drivers is prohibited.

6.5.3 USAC Race Control Frequency

Teams are required to monitor Race Control from Pit Lane before, during, and after sessions.

USAC Channels				
Race Control Team Broadcast (Primary)	Simplex	Analog	464.5500	516

Race Control Team Broadcast (Backup)	Simplex	Analog	461.2000	432
---	---------	--------	----------	-----

6.6 On-board Video & Streaming

All Cars are required to have a VBOX Video HD2 system installed and maintained as detailed in the Model Specific Technical Regulations. Cars are further permitted to use the GPX system for live video transmission. Other live video transmission systems are not permitted. Only Cars equipped with the GPX system may be featured in the Race Broadcast.

Additional cameras may be installed only with the approval of USAC and must be installed in a manner to satisfy the Technical Regulations.

Article 7: Refueling System

7.1 Scrutineering Fuel Collection

Fuel Collection Vessel must:

- Be clear
- Without any trolley or carriage system

- Flat bottomed
- Be supported without assistance on the USAC scale, before and after defueling the car for the purposes of weight measurement.

Fuel Pump Out Hoses – 2 separate hoses must be utilized for defueling activities:

- Fuel Drain
- Vent Return

These hoses must connect the collection vessel to the Car.

The drain line must use dry-break connections to the car and fixed (sealed) connections to the fuel collection vessel.

The vent line must utilize either a dry-break or temporary connection to the car and a fixed (sealed) connection to the fuel collection vessel.

The fuel drain hose must include a clear section of at least 250 mm near the collection vessel.

Article 8: Prohibited Changes to the Vehicle Systems After Approval

<p>8.1 Dimensions</p> <ul style="list-style-type: none"> • Reference Surface 	<p>8.8 Fuel System</p> <ul style="list-style-type: none"> • Fuel Cell • Fuel Lines • Fuel Sample Port • Refueling Receptacle
<p>8.2 Overall Dimensions</p> <ul style="list-style-type: none"> • Length • Width • Height • Wheelbase • Track • Overhang • Width 	<p>8.9 Brake System</p> <ul style="list-style-type: none"> • Master Cylinders • Brake Lines • Calipers • Rotors • Pads • Ducting • Anti-Lock Braking System
<p>8.3 Driver Interface</p> <ul style="list-style-type: none"> • Steering Wheel • Shifting Mechanism • Driver Adjustable Components 	<p>8.10 Steering System</p> <ul style="list-style-type: none"> • Lubricants
<p>8.4 Aerodynamic Elements</p> <ul style="list-style-type: none"> • General • Splitter • Wings • Rear Wing Gurney • Floor 	<p>8.11 Suspension System</p> <ul style="list-style-type: none"> • Geometry Elements • Dampers • Anti-Roll Bar • Third Elements

<p>8.5 Engine System</p> <ul style="list-style-type: none"> • Engine • Oiling System • Lambda • Engine RPM • Intake • Exhaust • Engine Control Unit (ECU) 	<p>8.12 Wheels and Tires</p> <ul style="list-style-type: none"> • Wheels • Wheel Attachment
<p>8.6 Drive System</p> <ul style="list-style-type: none"> • Clutch • Gearbox • Gears • Differential • Axles • Uprights 	<p>8.13 Electronics</p> <ul style="list-style-type: none"> • Data Logger • Wiring Loom • Sensors • Auxiliary Power Sources
<p>8.7 Cooling System</p> <ul style="list-style-type: none"> • Water System • Oil Cooling System 	



SFI Spec 45.2 Impact Padding

Participating Manufacturers - updated January 14, 2025

The below manufacturers are participating members in the SFI Performance Specifications Program for the above listed spec. Contact the individual manufacturer for specific part numbers that they certify to this spec:

Bald Spot Sports
4629 Northwestern Drive, Zionsville, IN 46077
(317) 537-7328 www.baldspotsports.com

BSCI, Inc.
170 Barley Park Lane, Mooresville, NC, 28117
(704) 664-3005 www.rollbarpadding.com

GET'M Performance Products, LLC
1566 W.G.Talley Rd, Alvaton, TN 42122
(270) 935-5334 www.getmgarage.com

Impact Foam Solutions
11142 Treynorth Dr., Cornelius, NC 28031
(704) 450-0724 www.impactfoam.com

ISP Seats
4502 Raceway Dr SW, Concord, NC, 28027
(704) 795-0403 www.ispseats.com

KAN Seat Works (Pro-Seat bead system)
Las Vegas, NV
(561) 563-2810 www.kanseatworks.com

Urethane Science, Inc.
(H&D Molding)
8357 Standustrial St., Stanton, CA, 90608
(714) 828-3210 www.hdmolding.com

**MATERIAUX POUR LES INSERTS DE SIEGES SPECIFIES PAR LA FIA
SEAT INSERT MATERIALS SPECIFIED BY THE FIA**

LISTE TECHNIQUE N° 50 / TECHNICAL LIST N° 50

Fabricant Manufacturer	Nom du matériau Material Name
BSCI INC. 170 Barley Park Lane Mooresville, NC 28115, USA Tel. (1) 704 664 3005 Fax (1) 704 660 1540	Ener-Core EC50 (orange)
SJG International Ltd Tything Road, Arden Forest Industrial Estate Alcester, Warwickshire B49 6ES, England Tel: +44 1789 763721	Zotefoam HD60
BASF 67056 Ludwigshafen Deutschland Tel +49 6216042829	Neopolene RG60
JSP Z. I. Le Bois Chevalier Route de Francières F 60190 Estrées-Saint Denis France Tel +33 34491 7007	ARPRO RG60

Note : Les inserts en mousse pour sièges doivent être obtenus par usinage d'une des mousses ci-dessus. Les inserts pour sièges moulés peuvent être autorisés à condition qu'ils conservent exactement les mêmes propriétés mécaniques que les mousses usinées. Ceci est de la responsabilité du fabricant.

Note: Seat foam inserts must be obtained through the machining process of one of the above foams. Casted seat inserts may be authorised provided that they keep exactly the same mechanical properties as the machined foams. This is the manufacturer's responsibility.